



Datasheet

August 2015

Jet Stream[®] MAX

Blow-in Glasswool Insulation

Description

Jet Stream MAX is an unbonded, glasswool insulation designed with optimal thermal properties and excellent coverage and blowing characteristics.

Application

Jet Stream MAX can be installed into both new build and existing ceilings. It can be used to form the total thermal solution or as an additional thermal layer to existing insulation.

Jet Stream MAX should only be installed by Approved Installers to ensure the highest quality and installed performance.

Features

Excellent thermal performance

- Jet Stream MAX provides excellent thermal performance due to a low thermal conductivity and a complete and consistent installation.

Acoustic performance

- Improves sound transmission class (STC) by between 4 and 10 points.

Performance

Thermal Conductivity

ASTM C 518 and AS/NZS 4859.1: 2002

Thermal Resistance

ASTM C 653 and AS/NZS 4859.1: 2002

Benefits

- High thermal performance.
- New and retrofit applications.
- Fills all gaps and voids, creating a complete thermal barrier against outside air.
- Excellent acoustic performance.
- Made with up to 80% post-consumer recycled glass.
- Fast, easy installation by Approved Installers.



CODEMARK™

AU - GM-CM30065 RevA1
NZ - GM-CM30068 RevA

Jet Stream® MAX

Sustainable

- Each bag contains a high percentage of recycled glass content.
- Carbon negative. When used as thermal insulation, Jet Stream MAX will recover the energy used to produce it within days of installation. It will continue to reduce carbon generation for as long as it is in place.

Installation

- Fast and easy to install with the added confidence of an Approved Installer.
- Easily fills hard to reach and low pitch roofs.

Nominal thickness (mm)	AU R-Value (m ² K/W)
50	1.0
75	1.5
100	2.0
125	2.5
160	3.1
180	3.5
205	4.0
255	5.0
306	6.0
360	7.0
410	8.0
460	9.0
510	10.0

Nominal thickness (mm)	NZ R-Value (m ² K/W)
50	1.0
75	1.5
100	2.0
125	2.5
160	3.2
180	3.6
205	4.1
255	5.2
310	6.3
360	7.3
410	8.4
460	9.4
510	10.4

Durability

- Non-combustible, non-corrosive.
- Will not rot, mildew or deteriorate.
- Will not sustain vermin.
- Will not settle.
- Consistent, reliable performance.
- Performs for the lifetime of the building.

Energy conservation

- Reduces energy usage and utility bills for heating and air conditioning.

Thermal performance

Jet Stream MAX provides a choice of R-Values based on the installed thickness and installed weight per square metre. The table above shows the minimum requirements for obtaining the desired R-Value.

The stated thermal resistance (R-Value) is provided by installing the required density at the thickness (per the manufacturer's instructions). Failure to install less than the required density and thickness will result in lower insulation R-Values.

Specification Guide

The insulation shall be Jet Stream MAX Insulation 0.051 W/mK (AU), 0.049 W/mK (NZ), 8-9kg/m³, CodeMark Certified to meet the provisions of the BCA. The product will be non-combustible, CFC/HCFC free, zero ODP and GWP, glasswool insulation with high post-consumer recycled glass content. It will be manufactured under Quality Assurance Standards ISO 9001:2008 and ISO 14001:2004 by Knauf Insulation and shall be installed in accordance with the instructions issued by them.

Jet Stream® MAX

Jet Stream MAX is designed to be installed at a target density of 8-9kg/m³. Refer to the thermal performance table for more details. Jet Stream MAX will achieve R-Values that with the use of NZS 4214 are able to meet the minimum requirements of NZS 4218 and the Energy Efficiency requirements of BCA for ceilings.

Engineered Blow-in Insulation System

Jet Stream MAX is an engineered solution which incorporates a system approach to the insulation of your ceiling space.

A range of accessories are supplied with the System to provide a range of solutions and performance checks.

Backed by the Approved Installer network, to provide confidence in the performance of the product.

Specification compliance

- ASTM and AS/NZS 4859.1 compliance.
- Fire Resistance (AS1530.1:1994 - non-combustible).
- US GREENGUARD Gold Certified and verified to be formaldehyde free.

Jet Stream MAX is manufactured with up to 80% post-consumer glass content and undergoes UL Environment verification every six months.

Technical data

- Does not exceed 25 Flame Spread, 50 Smoke Developed when tested in accordance with ASTM E 84 and CAN/ULC S102.2.

Critical radiant flux (ASTM E 970)

- Greater than 0.12 W/cm².

Moisture vapour absorption (ASTM C 1104)

- 5% maximum by weight.

Corrosion (ASTM C 764)

- No greater than sterile cotton.

Microbial growth (ASTM C 1338)

- Does not support microbial growth.

Non-combustibility

- Deemed to be non-combustible (AS 1530.1-1994).

Equipment required

To achieve the required R-Value, this product must be installed using an approved blowing machine and equipment. Installation must be complete inline with the system guidelines and by an Approved Installer.

Packaging

Jet Stream MAX is packaged in a strong, poly bag that offers excellent protection from abuse, dust and moisture. Knauf Insulation packages stack without slipping and are easy to handle and store.

Jet Stream® MAX

Jet Stream MAX satisfies the most stringent requirements for bio-solubility and will meet or contribute to meeting the following provisions of the:

Australia National Construction Code Series (NCC 2015) Building Code of Australia (BCA)

- BCA 2015 Volume 1 – Class 2 to 9 Buildings.
- Section J - Energy Efficiency: Performance Requirement JP1. Jet Stream MAX will satisfy this requirement.
- BCA 2015 Volume 2 – Class 1 and Class 10 Buildings.
- Part 2.6 Energy Efficiency: Performance Requirement P2.6.1. Jet Stream MAX will satisfy this requirement.
- Jet Stream MAX thermal resistance has been determined by AS/NZS4859.1.
- Jet Stream MAX is an acceptable solution in terms of the Australian Building Code.

New Zealand Building Code:

- Clause B2 DURABILITY: Performance B2,3,1(b) 15 years. Jet Stream MAX will meet this requirement.
- Clause E3 INTERNAL MOISTURE: Performance E3.3.1. Jet Stream MAX will contribute to meeting this requirement.
- Clause F2 HAZARDOUS BUILDING MATERIALS: Performance F2.3.1. Jet Stream MAX meets this requirement and will not present a health hazard to people.
- Clause H1 ENERGY EFFICIENCY: Performance H1.3.1(a) and H1.3.2 E. Jet Stream MAX will contribute to meeting these requirements.
- Jet Stream MAX thermal resistance has been determined by AS/NZS 4859.1.
- Jet Stream MAX is an acceptable solution in terms of the New Zealand Building Code.

Australia
Knauf Insulation Pty Ltd
Unit 1, 44 Borthwick Ave
Murarrie QLD 4172
Australia

New Zealand
Knauf Insulation Ltd
Building 1, Unit 2, 15 Accent Dr
East Tamaki Auckland 2013
New Zealand

Sales
(AU) 1800 562 834
(NZ) 0800 562 834

Technical Support
+61 7 3393 7300